

CRUSH-ALL BUCKET CRUSHER ATTACHMENT







- VERSATILE
- MOBILE
- SIMPLE AND EASY TO OPERATE!
- **ONE MAN OPERATION**
- **EFFICIENT**
- **CRUSHES ANYTHING!**
- PRODUCES BEAUTIFUL SPEC MATERIAL.
- EASY TO MAINTAIN.
- REVERSIBLE AND REPLACEABLE WEAR

PARTS.

- CAN SPLIT IN HALF FOR MAINTENANCE OR TRANSPORT.
- **MOUNTS ON EXCAVATORS FROM 20-25-**30-45 TONS.
- USES EXISTING EXCAVATOR HYDRAU-LICS / HAMMER KIT (*MOST CASES).
- INEXPENSIVE
- MADE IN USA!

*THE HIGHEST OUTPUT BUCKET CRUSHER IN THE WORLD!!!

WE GUARANTEE IT!! We average [2] full buckets per minute at 2" minus setting.

TIME IS MONEY! LOOK NO FURTHER!! FEED 24" CHUNKS ALL DAY!!

CRUSH-ALL® is an IMPACT or JAW crusher in a bucket. Fully ADJUSTABLE to make nearly any size you desire. RE-BAR and wire are no problem. Only two (2) reversible blow bars or jaw dies. Bars are available in a variety of materials. Jaw dies are made from manganese steel. CRUSH-ALL® is available in several models to fit nearly every application. Please refer to our "excavator requirement chart" when deciding what model CRUSH-ALL® will work for you. Don't worry about the pin connection. We supply replaceable bushings to adapt CRUSH-ALL® to nearly every pin size. Quick disconnect hitches are no problem. Hydraulically speaking, most excavators with a 3rd valve or hammer kit will operate CRUSH-ALL® with only minor modifications. Regardless, we provide all the necessary schematic diagrams you will need to plumb your machine if required. We make it simple and easy. Our in house hydraulic technicians are available to do complete installations including plumbing at your site or ours!

* 'Results based on CR75 & 125 will vary based on operator skill level and various other factors. Please consult your sales rep. for details.

Available Options

- "EXTREME DUTY" HYDRAULIC HOSE KIT
 - DUST SUPPRESSION

<u>CRUSH-ALL®</u>

SPECIFICATIONS & EXCAVATOR REQUIREMENTS

	CR55	CR75	CR95	CR125
CRUSHER TYPE	IMPACT	IMPACT	JAW	IMPACT
FEED OPENING (WIDTH X HEIGHT)	24" x 18"	33" x 25"	35" x 18"	43" x 32"
OUTPUT ADJUST. MIN./MAX.	3/8" / 3"	3/8" / 6"	3/4" / 6"	3/8" / 7"
OVERALL WEIGHT LBS	3000	5800	7900	12000
WIDTH	48"	62"	54"	78.5"
LENGTH	62"	81"	97"	104"
Неіонт	53"	60"	60"	74"
CAPACITY (YD3)	0.25	0.60	1.00	1.33
EXCAVATOR REQUIREMENTS				
METRIC TONS POUNDS US TONS	9 20,000 1 0	20 40,000 22	25 50,000 28	30 60,000 33
NECESSARY HYDR. FLOW RATE (GPM)	40	40	60	80
HP RATING	50	100+	100+	180+
MIN. / MAX HYDR. PRESSURE REQUIRED	3000 / 4000 PSI 206-275 BAR	4000 / 5000 PSI 275-345 BAR	3400 / 3600 PSI 235-248 BAR	4000 / 5000 PSI 275-345 BAR

RETURN PRESSURE 1 D-13 BAR 21-35 BAR 1 1-16 BAR 21-35 BA
* All photos, specifications, and/or data is approximate and subject to change without notice. Information provided in this brochure is general and for the purpose of presenting an overview of the company, its abilities, and products. Use of material without the express written consent of R.R. is strictly prohibited and subject to penalties.

300 / 500 PSI

150 / 200 PSI



MIN. / MAX.





300 / 500 PSI

21-35 BAR

CRUSH-AL

150 / 225 PSI

PORCELAIN

THE R.R. DIFFERENCE

- VALUE OUR PRICES ARE UNBEATABLE
- SAVINGS BUY FACTORY DIRECT, NO MIDDLEMAN
- EXPERTISE WE INVENT, MANUFACTURE & SELL WORLDWIDE
- ARIETY FROM ATTACHMENTS TO COMPLETE CRUSHING PLANTS, WE OFFER THE LARGEST RANGE OF PRODUCTS TO MATCH ANY BUDGET

FOR MORE INFORMATION OR TO SCHEDULE A DEMO: 5550 CHARLOTTE HWY . LANCASTER, SC . 29720 (803)416-5200, PHONE . (803) 416-5202, FAX SALES@RREQUIPMENT.COM . WWW.RREQUIPMENT.COM